

## Three wheel static roller

## Description of Three Wheel Static Roller

The three **wheel static roller** are capable of compacting grave, macadam, asphalt concrete, non0cohesive or less cohesive soils, lime and cinder as well as rolling of foundations of public squares and pavements.

## Main Features of Three Wheel Static Roller

- 1. Compact construction and small turning radius, with smooth finished surface.
- 2. The disk brake and change-over clutch are reliable and durable.
- 3. The hydraulic steering system assures easy manipulation.
- 4. The driving roll is made of cast steel. With thickness increased for sturdy and wear-resisting.
- 5. The comfortable seat and excellent visibility feature its rational design.
- 6. Either a cab or a canopy is available to buyer's option.

## Main Specification of Three Wheel Static Roller

Model	3YJ8/10	3YJ8/12	3YJ10/12	
Weight (t)				
Without Ballast	8	8	10	
With Ballast	10	12	12	

[			
Roll Diameter (mm)		1	
Front Roll (for steering)	1060	1060	1060
Rear Roll (for driving)	1500	1600	1600
Roll width (mm)			
Front Roll	1250	1250	1250
Rear Roll	500×2	500×2	500×2
Linear Pressure (N/CM)			
Rear Roll			
Without Ballast	>520	>520	>650
With Ballast	>650	>730	>780
Travel speed (km/h)			
I speed	2	1.9	1.9
II speed	3.5	3.2	3.2
III speed	8	7.5	7.5
Min. Turning radius (mm)	≦5500	≦6000	≦6000
Grade ability	1:5	1:5	1:5
Wheel Base (mm)	2500	2800	2800
Ground Clearance (mm)	270	300	320
Diesel Engine			
Туре	495AY	4135K-20	C 4135K-2C
Rated Power	36	58	58
Rated speed	2000	1500	1500
Overall Dimension(mm) L	_×W×H		Υ
Cabin	4343×2116×2717	4664×2116×	
Canopy	4460×2116×2613 50	39×2116×2663	4760×2116×2663

World Equipment is a professional Chinese manufacturer and supplier of three **wheel static roller**. In over 10 years, we keep improving our products to make them better adapt to the market. We offer 3 types, namely, 3YJ8/10 (8T/10T), 3YJ8/12 (8T/12T), and 3YJ10/12 (10T/12T), to satisfy the clients' different demands. If you need three **wheel static roller**, contact us without hesitation.